



FEATURES

- 32Bit ARM9
- 64MB DDR2 SDRAM
- SDHC/MMC x 1
- 256MB NandFlash
- RS232 / 485 x 2
- USB-A x 1, USB-B x 1
- 10/100Base, RJ 45 x1

SPECIFICATIONS

SYSTEM	
Processor	32Bit ARM9
System Memory	64MB DDR2 SDRAM
Ethernet	10/100Base, RJ 45 x1
I/O Port	USB-A x 1 USB-B x 1 RS232/485 x 1 Power Input x 1
Storage Disk Drive	256MB NandFlash SDHC/MMC x 1
Expansion Slot	SDHC/MMC x 1
Operating System Support	WinCE/Linux

LCD

Display Type	7" TFT LED Backlight
Max Resolution	1024x600
Max. Colors	16.7M
Luminance	300cd/m2
Viewing Angle	160°(H), 160°(V)
Back Light MTBF (Hours)	>20000H(25°C)

TOUCH SCREEN

Type	4-Wire Resistive
Light Transmission	More than 81%
Life Time	250 g Dynamics , 2 Million Times

POWER SUPPLY

DC Input	DC 20 ~ 28Vdc(24Vdc Rated)
----------	----------------------------

ENVIRONMENTAL

Operating Temperature	-10°C ~ 50°C
Storage Temperature	-20°C ~ 65°C
Storage Humidity	10% ~ 90% Relative Humidity, Non-condensing

MECHANICAL

Construction	ABS Plastic
Mounting	Panel Mount
Dimensions	198.8x137.8x47.5mm
Weight	0.7 kg

DIMENSION (Unit: mm)

