



FEATURES

- Intel Bay Trail J1900 2GHz
- 2GB DDR3 1333MHz SO-DIMM, Up to 8GB
- USB 2.0 x 2
- DB-9 For RS232x 5, RS232/485 x 1
- 10/100/1000Base, RJ 45 x 2
- DC_IN 12V(Optional 6~30V)
- Support Windows XP, Windows 7, Linux

SPECIFICATIONS

SYSTEM	
Processor	Intel Bay Trail J1900 2GHz
System Memory	2GB DDR3 1333MHz SO-DIMM, Up to 8GB
Ethernet	10/100/1000Base, RJ 45 x 2
I/O Port	USB 2.0 x 2 DB-9 For RS232x 5, RS232/485x 1 VGAx 1 LINE-out x 1 Power Input x 1
Storage Disk Drive	SATA2.5"SSD/HDD/MSATA
Expansion Slot	-
Operating System Support	Windows7/8/10、Linux/Embedded

LCD

Display Type	19"XGA TFT LED backlight
Max. Resolution	1280x1024
Max. Colors	16M
Luminance	350cd/m ²
Viewing Angle	160°(H), 160°(V)
Back Light MTBF (Hours)	50000

TOUCH SCREEN

Type	Heat 5-wire, analog resistive
Light Transmission	More Than 81%
Life Time	35 Million Times Click

POWER SUPPLY

DC Input	DC_IN 12V(Optional 6~30V)
----------	---------------------------

ENVIRONMENTAL

Operating Temperature	0°C ~ 60°C
Storage Temperature	-20°C ~ 70°C
Storage Humidity	10% ~ 95%@40°C Relative Humidity, Non-condensing

MECHANICAL

Construction	The Panel Is Made Of Aluminum-magnesium Alloy, And The Shell Is Made Of Sheet Metal
Mounting	VESA / Panel Embedded Mount
Dimensions	435x360x55mm
Weight	-

DIMENSION (Unit: mm)

