



FEATURES

- Atom N2600 dual-core 1.6 Hz Energy-saving Processor
- 2GB DDR3 1066MHz SDRAM
- USB 2.0 x 2
- DB-9 For RS232 x 5, RS485 x 1
- 10/100/1000Base, RJ 45 x2
- DC 12V(Optional 6-30V)
- Support Windows XP, Windows VISTA, Windows 7, Linux

SPECIFICATIONS

SYSTEM	
Processor	Atom N2600 Dual-core 1.6 Hz Energy-saving Processor
System Memory	2GB DDR3 1066MHz SDRAM
Ethernet	10/100/1000Base, RJ 45 x 2
I/O Port	USB 2.0 x 2 DB-9 For RS232 x 5, RS485 x 1 LINE-out port x 1 Power Input x 1
Storage Disk Drive	Support mSATA
Expansion Slot	-
Operating System Support	Windows VISTA, Windows XP, Windows 7, Linux

LCD

Display Type	19"VGA TFT LED backlight
Max Resolution	1280x1024
Max. Colors	16M
Luminance	350cd/m2
Viewing Angle	160°(H), 160°(V)
Back Light MTBF (Hours)	50000

TOUCH SCREEN

Type	Heat 5-wire, analog resistive
Light Transmission	More Than 81%
Life Time	35 Million Times Click

POWER SUPPLY

DC Input	DC 12V(Optional 6-30V)
----------	------------------------

ENVIRONMENTAL

Operating Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10%~ 95%@40°C Relative Humidity, Non-condensing

MECHANICAL

Construction	The Panel Is Made Of Aluminum-magnesium Alloy, And The Whole Surface Of The Shell Is Processed By Aluminum-magnesium Alloy
Mounting	VESA / Panel Embedded Mount
Dimensions	459x366x56mm
Weight	7.7KG

DIMENSION (Unit: mm)

