



FEATURES

- Socket rPGA988, Intel 3rd Generation Core i7/i5 Celeron Processor
- 204-pin Dual-channel DDR3 1066/1333/1600 MHz SODIMM x 2, Up to 8GB
- USB 2.0 x 2, USB 3.0 x 4
- DB-9 for 1xRS-232, 1xRS-232/485
- 10/100/1000Base, RJ 45 x2
- DC_IN 12~24V
- Support Windows 2000/ XP/ VISTA/ 7, Linux

SPECIFICATIONS

SYSTEM	
Processor	Socket rPGA988, Intel 3rd Generation Core i7/i5 Celeron Processor
System Memory	204-pin Dual-channel DDR3 1066/1333/1600MHz SODIMM x 2, Up to 8GB
Ethernet	10/100/1000Base, RJ 45 x2
I/O Port	USB 2.0 x 2, USB 3.0 x 4 DB-9 for RS-232x 1, RS-422/485x 1 PS2 x 2 LINE-out x 1 Power Input x 1
Storage Disk Drive	SATA 2.5"SSD/HDD/ DOM
Expansion Slot	PCI-Express [x16] x 1 MiniCard x 1 CFast x 1, TPM x 1
Operating System Support	Windows 2000/ XP/ VISTA/ 7, Linux

LCD	
Display Type	19"XGA TFT LED Backlight
Max Resolution	1280x1024
Max. Colors	16M
Luminance	350cd/m2
Viewing Angle	160°(H), 160°(V)
Back Light MTBF (Hours)	50000

TOUCH SCREEN	
Type	Heat 5 Wire Analog Resistive
Light Transmission	More Than 81%
Life Time	35 Million Times Click

POWER SUPPLY	
DC Input	DC_IN 12~24V

ENVIRONMENTAL	
Operating Temperature	0°C ~ 60°C
Storage Temperature	-20°C ~ 70°C
Storage Humidity	10% ~ 95%@40°C Relative Humidity, Non-condensing

MECHANICAL	
Construction	The Panel Is Made Of Aluminum-magnesium Alloy, And The Whole Surface Of The Shell Is Processed By Aluminum-magnesium Alloy
Mounting	VESA / Panel Embedded Mount
Dimensions	460 x 365 x 96.5mm
Weight	5.0KG

DIMENSION (Unit: mm)

