



### FEATURES

- Onboard 2nd/3rd Generation Intel Celeron1037U CPU
- 1 x 204 Pin 4GB DDR3 SO-DIMM
- RS-232 x 4, RS-232 /4 85 x 1,RS-232 / 422 / 485 x 5
- 10 / 100 / 1000Base, RJ 45 x 2
- 2.5" SATA x 1,mSATA x 1
- DC\_12~24V
- USB x 6, SIM x 1(Optional), 16-bit DIO x 1(Optional)

### INTRODUCTION

EC8105 powered by 2nd/3rd Generation Intel Celeron1037U CPU with high graphic and computing performance. With its outstanding performance,EC8105 can be utilized within industrial automation, self-service machines like factory automation and ETC. EC8105 support multiple I/O especially contains up to 10 x COM (RS-232x 4,RS-232/485x 1,RS-232/422/485x 5) and 6 x USB. Other than that, EC8105 has a DC input from 12V to 24V, a wide operating temperature and a PCI -104 expansion, it is therefore designed to meet most application requirements.

### SPECIFICATIONS

SYSTEM CORE	
Processor	On Board 2nd/3rd Generation Intel Celeron1037U CPU
Chipset	Intel BD82NM70
System memory	1x204Pin 4GB DDR3 SO-DIMM
I/O INTERFACE	
Ethernet	10/100/1000Base, RJ 45 x 2
USB	USB x 6
Video Port	VGA x 1,18/24-bit LVDS x 1(Optional),HDMI x 1
Serial Port	RS-232 x 4, RS-232/485 x 1, RS-232/422/485 x 5
Audio	LINE OUT x 1 , MIC-IN x 1
STORAGE INTERFACE	
SATA HDD	2.5" SATA x 1
mSATA	mSATA x 1
EXPANSION BUS	
Mini PCI-E	-
ExpandCable I/O	PCI-104 x 1

POWER SUPPLY	
DC Input	DC_12~24V
MECHANICAL	
Dimension	246 x 209 x 93mm (W x D x H)
Weight	-
Mounting	Desktop Or Wall Mount
ENVIRONMENTAL	
Operating Temperature	-20°C ~ 60°C
Storage Temperature	-40°C ~ 80°C
Humidity	5%~95% @ 40°C, non-condensing
Vibration	Operatng, 5 Grms, 5-500 Hz, 3 Axes
Shock	Operatng, 50 Grms, Half-sine 11 ms Duration
Certification	CE/FCC