





## **FEATURES**

- Onboard1st Intel Core i7/i5/i3 CPU
- 2 x 204 Pin 4GB DDR3 SO-DIMM
- RS-232x 2,RS-232/485x 1,RS-232/422/485x 3
- 10/100/1000Base, RJ 45 x 2
- 2.5"SATA x 1
- mPCIEx1 x 1, PCI x 1(Optional PCIE x 1),PCI-104 x 1
- USBx 6,SIM x 1(Optional),16-bit DIOx 1(Optional)
- 18-24bit LVDS x 1(Optional),LPTx 1(Optional)

## **INTRODUCTION**

EC8506 powered by Onboard1st Intel Core i7/i5/i3 CPU with high graphic and computing performance. With its outstanding performance, EC8506 can be utilized within industrial automation, self-service machines like factory automation and ETC. EC8506support multiple I/O especially contains up to COM x 6 (RS-232 x 2,RS-232/485 x 1,RS-232/422/485 x 3) and USB x 6. Other than that, EC8506 has a DC input from 12V to 24V, a wide operating temperature , a PCI and a PCI-104 expansion, it is therefore designed to meet most application requirements.

## **SPECIFICATIONS**

Onboard 1st Intel Core i7/i5/i3 CPU
Intel BD82HM55
1x204Pin 4GB DDR3 SO-DIMM
10/100/1000Base, RJ45 x 2
USB x 6
VGA x 1,HDMI x 1
RS-232x 2,RS-232/485x 1,RS-232/422/485x 3
LINE OUT x 1 , MIC-IN x 1
2.5" SATA x 1
-
mPCIEx1 x 1(Optional mSATA x 1)
PCIx 1(Optional PCIEx 1),PCI-104x 1

POWER SUPPLY	
DC Input	DC_12~24V
MECHANICAL	
Dimension	246 x 209 x 114mm (W x D x H)
Weight	-
Mounting	Desktop Or Wall Mount
ENVIRONMENTAL	
Operating Temperature	-20°C ~ 60°C
Storage Temperature	-40°C ~ 80°C
Humidity	5%~95% @ 40°C, non-condensing
Vibration	Operatng, 5 Grms, 5-500 Hz, 3 Axes
Shock	Operatng, 50 Grms, Half-sine 11 ms Duration
Certification	CE/FCC