

EC8708

On Board 2nd/3rd Generation Intel Core i7/i5/i3
Celeron Processor



FEATURES

- On Board 2nd/3rd Generation Intel Core i7/i5/i3 Celeron Processor
- 1 x 204 Pin 4GB DDR3 SO-DIMM
- RS-232x 2,RS-232/485x 1,RS-232/422/485x 3
- 10/100/1000Base, RJ 45 x 2
- 1 x 2.5"SATA , 1 x CF(Optional)
- mPCIEx1 x 1(Optional mSATA x 1) , PCI x 3 , PCI-104 x 1
- SIM x 1(Optional),16-bit DIO x 1(Optional) ,LPT x 1(Optional)

INTRODUCTION

EC8708 powered by 2nd/3rd Generation Intel Core i7/i5/i3 Celeron Processor with high graphic and computing performance. With its outstanding performance,EC8708 can be utilized within industrial automation, self-service machines like factory automation and ETC. EC8708 support multiple I/O especially contains up to 6 x COM (RS-232x 2,RS-232/485x 1,RS-232/422/485x 3) and 6 x USB. Other than that, EC8708 has a DC input from 12V to 24V, a wide operating temperature and three PCI expansions; it is therefore designed to meet most application requirements.

SPECIFICATIONS

SYSTEM CORE	
Processor	On Board 2nd/3rd Generation Intel Core i7/i5/i3 Celeron Processor
Chipset	Intel BD82HM76
System memory	1x204Pin 4GB DDR3 SO-DIMM
I/O INTERFACE	
Ethernet	10/100/1000Base, RJ 45 x 2
USB	USB x 6
Video Port	VGA x 1,18/24-bit LVDS x 1(Optional),HDMI x 1
Serial Port	RS-232x 2,RS-232/485x 1,RS-232/422/485x3
Audio	LINE OUT x 1 , MIC-IN x 1
STORAGE INTERFACE	
SATA HDD	2.5" SATA x 1
mSATA	-
EXPANSION BUS	
Mini PCI-E	mPCIEx1 x 1(Optional mSATA x 1)
ExpandCable I/O	PCI x 3, PCI-104x1

POWER SUPPLY	
DC Input	DC_12~24V
MECHANICAL	
Dimension	246 x 209 x 153mm (W x D x H)
Weight	-
Mounting	Desktop Or Wall Mount
ENVIRONMENTAL	
Operating Temperature	-20°C ~ 60°C
Storage Temperature	-40°C ~ 80°C
Humidity	5%~95% @ 40°C, non-condensing
Vibration	Operatng, 5 Grms, 5-500 Hz, 3 Axes
Shock	Operatng, 50 Grms, Half-sine 11 ms Duration
Certification	CE/FCC